5.5 HPF Underlay High Performance Hardboard Underlay

Product Brochure

5.5 HPF Hardboard Underlay is an environmentally friendly, high performance fibre board underlay manufactured in Australia to E0 standards.

Used over particleboard, strip timber, plywood and concrete flooring, 5.5 HPF Underlay provides a strong flat ultra smooth base for resilient floor coverings.









FEATURES

- · Smart cost saving solution
- E0 and environmentally friendly
- Easy to score and snap with clean snap lines
- Ultra smooth and strong indent resistant surface
- · Double sided feature adds strength and versatility
- Minimum face reaction to staples means less sanding and preparation work required
- Complies with Australian Standards AS 1884

SPECIFICATIONS

Technical Data

5.5mm
1200 x 900
850 kg/m3
4.67 kg/m2
5.04 kg/sheet
1200 kPa
40 MPa
4000 MPa

Size Tolerances

Thickness	+/- 0.15mm
Length & Width	+/- 1.5mm
Squareness (Diagonal Variation)	2.0mm max

INSTALLATION

Scan the QR code for installation guide.







FLOORING

With an extensive range of options, Australian Panels can accommodate subfloors, suspended floors in multi-storey construction, building additions and extensions along with oversized commercial flooring spaces.

PANELLING

Made with the same durable materials used in our market leading STRUCTAflor particleboard flooring products, the new and exciting panelling products consist of STRUCTApanel H2 9mm Treated Structural and 12mm Non-Structural Panelling.

BOARD

Our CUSTOMwood (MDF) and CUSTOMpine (Particleboard) ranges both have Raw and Laminated options that make a versatile product to use in interior fitout solutions. Whether it be for the reliable quality that guarantees uniformity in size, density, and strength or for applications that are subject to humidity or moisture, such as bathroom vanities and kitchen cupboards, Australian Panels has the solution.

MOULDINGS

Manufactured in a wide range of design styles our mouldings and architraves are produced from premium grade MR CUSTOMwood MDF. They are pre-primed and ready to use on internal decorative trims, such as door jambs and skirtings and are guaranteed not to warp, buckle or split.









